



**BORAL**  
WINDOWS

Krestmark® Collection



NEW CONSTRUCTION

**250**  
SERIES

# 250 SERIES

The Series 250 casement, awning and picture windows are primarily used for new construction. The actual unit size, however, is 1/2" under call out and is manufactured in some of the most common sizes used for replacement window installations. For some of these replacement applications the integral nail fin could be removed. Note: All picture windows, shapes and one-frame glass larger than 30 square feet will come with Tempered Glass as standard for safety reasons. All additional charges for Tempered Glass will automatically be applied.



## FEATURES

- Multi-chambered, extruded vinyl frame and sash provide stability with excellent strength, thermal-resistant properties and is extremely low maintenance.
- Fusion-welded corners in frame and sash provides strength and virtually eliminates air and water infiltration.
- Single, twin and triple casements, awnings, picture combinations, 1/4 and 1/2 rounds, arches and eyebrows are available as mullied transoms.
- 3/4" insulated glass, warm-edge spacer, energy-efficient LoE coating option. Type and look of warm edge spacer may vary.
- Multi-point locking hardware with hinged-side snubber, folding handle to minimize window treatment interference, and sash alignment wheel.
- Dual-durometer, double weather strip, energy-efficient system with welded corners for excellent performance and resistance to weather penetration.
- Certifications of all products tested are done to meet or exceed national testing standards by NFRC and AAMA; Energy Star® partner; TDI approval.

## OPTIONS

- Argon-enhanced glass improves energy efficiency.
- Tempered obscure, bronze or grey glass; 3/4" dual-insulated clear glass.
- Grille patterns: 3/4" Colonial, Prairie, 1" Contoured and 1-1/8" Simulated Divided Lite.
- Factory mullied or stacked units and field mull accessories.


## PERFORMANCE DATA

Vinyl Casement/Awning and Picture Windows, 250 Series							
Glass Dual 3/4" OA Insulated	Csmt/Awning U-F SHGC VT		Picture Window U-F SHGC VT		Energy Star meets guideline in these zones		
E66 LoE Air no grilles	.29	.19	.43	.29	.22	.50	North Central
E66 LoE Air w/ grilles	.29	.17	.38	.29	.20	.45	South Central
E66 LoE Argon no grilles	.26	.18	.43	.25	.21	.50	Southern
E66 LoE Argon w/ grilles	.26	.17	.38	.25	.19	.45	



AAMA Performance: 3050 - R50; 3060 - R30.  
Standard windows meet or exceed 2016 Texas Adopted State Energy Code.

## CARDINAL IG

## COLOR OPTIONS



## GRILLE OPTIONS



You may qualify for a tax credit when you replace your existing windows. For more information, go to [energystar.gov](http://energystar.gov)



For information about measuring & installing Krestmark Collection windows, visit our website: [www.boralwindows.com](http://www.boralwindows.com)  
3950 Bastille Road, Suite 100 • Dallas, TX 75212 • PH: 214.237.5055

